



L300 SERIES - CRIMP ALL SS LIQUID FILLED PRESSURE GAUGE

L300 Series is All SS gauge with crimped ring, glycerine filled /silicon oil filled/dry, Bottom Mount.

L300 Series has SS304 Case, SS316L tube and connection, they are filled with glycerin or silicon oil or dry which can be used in most corrosive atmospheres, vibration and pulsation environments, food industry, water supplier, medical, etc.

Material Feature

Case	SS304, Polished	Connection	SS316L NPT/BSP/BSPT/Metric
Ring	SS304, Polished	Thread Size	1/8", 1/4", 3/8", 1/2"
Window	Polycarbonate/ Tempered Glass	Connection Type	1 Part/2 Parts
Dial	Aluminium	Movement	SS304
Pointer	Aluminium	Bourdon Tube	SS316L
Accuracy	2-1-2/1.6%/1.0%*	Pres. Range	VAC~9PSI~15000PSI

Other details can be customized according to your special requirements.

For example: **L300S-252**

(63mm All SS pressure gauge, silicon oil filled, SS304 case with crimped ring, SS316L tube and connection, Bottom mount, **one pc construction**, 1/4"NPT)



For example: **L300S-404**

(100mm All SS pressure gauge, silicon oil filled, SS304 case with crimped ring, SS316L tube and connection, Bottom mount, **two pcs construction**, 1/2"NPT)

