



L201 SERIES - CRIMP SS CASE LIQUID FILLED PRESSURE GAUGE

L201 Series has SS304 case with crimped ring, brass internals and connection, Back Mount.

They are filled with glycerin or silicon oil or dry which can be used to resist vibration and pulsation. These gauges are suited to a broad range of plant, process, hydraulic, fluid power, etc.

Material Feature

Case	SS304, Polished	Connection	Brass NPT/BSP/BSPT/Metric
Ring	SS304, Polished	Thread Size	1/8", 1/4", 3/8", 1/2"
Window	Polycarbonate/ Tempered Glass	Connection Type	1 Part
Dial	Aluminium	Movement	Brass
Pointer	Aluminium	Bourdon Tube	Phosphorus Bronze
Accuracy	2-1-2/1.6%/1.0%	Pres. Range	VAC~9PSI~15000PSI

Other details can be customized according to your special requirements.

For example: **L201S-252**

(63mm, silicon oil filled, SS case with crimped ring, **Back mount**, one part brass connection, 1/4"NPT)



Front



Side



Back

For example: **L201S-252-FF**



63mm, silicon oil filled, SS case with crimped ring, **Back mount with Front Flange**, one part brass connection, 1/4"NPT

For example: **L201S-252-U**



63mm, silicon oil filled, SS case with crimped ring, **Back mount with U-Clamp**, one part brass connection, 1/4"NPT